



**EVERLIGHT ELECTRONICS CO.,LTD.**

# DATA SHEET

**PART NO. : 19-217/R6C-P1Q2/3T**

**DATE :**

**DEPARTMENT : R.D.3**

**REVISION : 1.0**

<b>RECEIVED</b>			
MASS PRODUCTION			
PRELIMINARY			
CUSTOMER DESIGN			
DEVICE NUMBER : DSE-197-B01			
PAGE : 10			
CUSTOMER	DESIGNER	CHECKER	APPROVER
	JESSICA CHANG	JEFF TSAI	CHARLES CHANG

REV	DESCRIPTION	RELEASE DATE

**Package Type:**

SMD For PCB Type

11-21	19-215
12-21	19-215A
12-215	19-217A
15-21	22-21
15-215	23-21
16-213	23-21B
17-21	24-21
17-215	25-21
19-21	27-21
19-21A	42-21

**Dominant Wavelength Groups:**

According to the difference wavelength to define

None: No definition

- A : Standard wavelength definition.
- B : Range of wavelength definition is more narrowly than group A.
- C : Range of wavelength definition is more narrowly than group A, but the value is different with group B.
- F : The wavelength definition in special specification.

The dominant wavelength data did not including ±1nm testing tolerance.

**Test Forward Current:**

- None: 20 mA
- Y : 5 mA
- Z : 10 mA

**Taping Quantity:**

- 1: 1000 pcs (Taping)
- 2: 2000 pcs (Taping)
- 3: 3000 pcs (Taping)
- 5: 5000 pcs (Taping)
- C : 1500 pcs (Taping)
- D : 10000 pcs (Taping)

**Packing Method :**

- A: Reverse-side placement (Anode toward the sprocket hole)
- B: Reverse-side placement (Anode toward the sprocket hole)
- C: Right-side placement
- D: Right-side placement (Anode toward the sprocket hole)
- T: Top-side placement
- R: Top-side placement (Anode toward the sprocket hole)

19 - 21

/

B

H

C

-

A

N1

P2

M

/

3

T

**Emission Color:**

R: Red

(λ d: 640nm, 630nm, 625nm)

S: Sunset Orange

(λ d: 615nm, 605nm)

Y: Yellow

(λ d: 595nm, 590nm)

G: Green

(λ d: 570nm, 565nm, 560nm, 525nm, 505nm)

B: Blue

(λ d: 470nm)

W: White x=0.32  
y=0.31

The ordinal number that base on diffece electro-optical characteristics within chip.

1,2 ..... 7,8,9,  
A,B.....X,Y,Z

**Resin Color:**

- C: Water Clear
- W: White Diffused
- D: Diffused

**Luminous Intensity Groups:**

- C0: 0.28 ... 0.45
- D0: 0.45 ... 0.70
- E0: 0.70 ... 1.1
- F0: 1.1 ... 1.8
- G0: 1.8 ... 2.8
- H0: 2.8 ... 4.5
- J0: 4.5 ... 7.2
- K0: 7.2 ... 11.5
- L ⇒ L1: 11.5 ... 14.5
- L2: 14.5 ... 18.0
- M ⇒ M1: 18.0 ... 22.5
- M2: 22.5 ... 28.5
- N ⇒ N1: 28.5 ... 36.0
- N2: 36.0 ... 45.0
- P ⇒ P1: 45.0 ... 57.0
- P2: 57.0 ... 72.0
- Q ⇒ Q1: 72.0 ... 90.0
- Q2: 90.0 ... 112

- R ⇒ R1: 112 ... 140
- R2: 140 ... 180
- S ⇒ S1: 180 ... 225
- S2: 225 ... 285
- T ⇒ T1: 285 ... 360
- T2: 360 ... 450
- U ⇒ U1: 450 ... 565
- U2: 565 ... 715
- V ⇒ V1: 715 ... 900
- V2: 900 ... 1120
- W ⇒ W1: 1120 ... 1420
- W2: 1420 ... 1800
- X ⇒ X1: 1800 ... 2250
- X2: 2250 ... 2850
- Y ⇒ Y1: 2850 ... 3600
- Y2: 3600 ... 4500

Unit: mcd

The luminous intensity data did not including ±15% testing tolerance.

**Forward Voltage Groups:**

None: No definition

The VF definition as follows:

		Unit: V		
Forward Voltage Group	Bin	Min.	Max.	
C	A	00	1.55	1.75
	B	0	1.75	1.95
		1	1.95	2.15
		2	2.15	2.35
		3	2.35	2.55
M	D	4	2.55	2.75
	E	5	2.75	3.05
		6	3.05	3.35
		7	3.35	3.65
		8	3.65	3.95
N	R	9	2.50	2.70
	J	10	2.70	2.90
	F	11	2.90	3.10
	K	12	3.10	3.30
		13	3.30	3.50
P	H	14	3.50	3.70
		15	2.70	2.85
		16	2.85	3.00
		17	3.00	3.15
		18	3.15	3.30

The forward voltage data did not including ±0.1V testing tolerance.

# ANNEX



EVERLIGHT ELECTRONICS CO., LTD.

REV.: 1.3

PAGE: 1/1

## ■ Dominant Wavelength Groups:

<b>R3,R6,R9</b>				
Dom . Wavelength Of Group	Range			
	Bin	Min.	Max.	Unit
A	E4	617.5	621.5	nm
	E5	621.5	625.5	nm
	E6	625.5	629.5	nm
	E7	629.5	633.5	nm

<b>R7</b>				
Dom . Wavelength Of Group	Range			
	Bin	Min.	Max.	Unit
A	E6	625.5	629.5	nm
	E7	629.5	633.5	nm
	E8	633.5	637.5	nm

<b>R8</b>				
Dom . Wavelength Of Group	Range			
	Bin	Min.	Max.	Unit
A	E7	629.5	633.5	nm
	E8	633.5	637.5	nm
	E9	637.5	641.5	nm
	E10	641.5	645.5	nm

## ■ Forward Voltage Groups:

Forward Voltage Groups				Range			
				Bin	Min.	Max.	Unit
A				00	1.55	1.75	v
				0	1.75	1.95	v
B				1	1.95	2.15	v
				2	2.15	2.35	v
C				3	2.35	2.55	v
				4	2.55	2.75	v
D				5	2.75	3.05	v
				6	3.05	3.35	v
E				7	3.35	3.65	v
				8	3.65	3.95	v
9				9	2.50	2.70	v
J				10	2.70	2.90	v
				11	2.90	3.10	v
K				12	3.10	3.30	v
				13	3.30	3.50	v
L				14	3.50	3.70	v
				15	2.70	2.85	v
M				16	2.85	3.00	v
				17	3.00	3.15	v
N				18	3.15	3.30	v
				19			

## Technical Data Sheet

### 0.4mm Height Flat Top LED

#### 19-217/R6C Series

#### Features

- Package in 8mm tape on 7" diameter reel.
- Compatible with automatic placement equipment.
- Compatible with infrared and vapor phase reflow solder process.
- Mono-color type.

#### Descriptions

- The 19-217 SMD Taping is much smaller than lead frame type components, thus enable smaller board size, higher packing density, reduced storage space and finally smaller equipment to be obtained.
- Besides, lightweight makes them ideal for miniature applications. etc.

#### Applications


- Automotive: backlighting in dashboard and switch.
- Telecommunication: indicator and backlighting in telephone and fax.
- Flat backlight for LCD, switch and symbol.
- General use.




#### Device Selection Guide

Part No.	Chip		Lens Color
	Material	Emitted Color	
19-217/R6C	AlGaInP	Brilliant Red	Water Clear

Package Outline Dimensions



For reflow soldering (propose)



**Note:** The tolerances unless mentioned is  $\pm 0.1\text{mm}$  , Angle  $\pm 0.5^\circ$  ,Unit = mm

**Absolute Maximum Ratings (Ta=25°C)**

Parameter	Symbol	Rating	Unit
Reverse Voltage	V <sub>R</sub>	5	V
Forward Current	I <sub>F</sub>	25	mA
Operating Temperature	T <sub>opr</sub>	-40 ~ +85	°C
Storage Temperature	T <sub>stg</sub>	-40 ~ +90	°C
Soldering Temperature	T <sub>sol</sub>	260 (for 5 seconds)	°C
Electrostatic Discharge	ESD	2000	V
Power Dissipation	P <sub>d</sub>	60	mW
Peak Forward Current (Duty 1/10 @1KHz)	I <sub>F</sub>	60	mA

**Electro-Optical Characteristics (Ta=25°C)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Peak Wavelength	$\lambda_p$	----	632	----	nm	I <sub>F</sub> =20mA
Dominant Wavelength	$\lambda_d$	----	624	----	nm	
Spectrum Radiation Bandwidth	$\Delta\lambda$	----	20	----	nm	
Viewing Angle	$2\theta_{1/2}$	----	120	----	deg	
Forward Voltage	V <sub>F</sub>	----	2.0	2.4	V	
Reverse Current	I <sub>R</sub>	----	----	10	$\mu A$	V <sub>R</sub> =5V







**19-217/R6C Series Explain Of Luminous Intensity:**
**IF=20mA**

Part No.	Parameter	Symbol	Typ.	Bin	Min.	Max.	Unit
19-217/R6C-P1Q2	Luminous Intensity	Iv	75	P1	45.0	57.0	mcd
				P2	57.0	72.0	
				Q1	72.0	90.0	
				Q2	90.0	112	
19-217/R6C-Q1R1	Luminous Intensity	Iv	100	Q1	72.0	90.0	mcd
				Q2	90.0	112	
				R1	112	140	
19-217/R6C-Q2R2	Luminous Intensity	Iv	135	Q2	90.0	112	mcd
				R1	112	140	
				R2	140	180	

**Note:**

 The luminous intensity data did not including  $\pm 15\%$  testing tolerance.

Typical Electro-Optical Characteristics Curves





**Label explanation**


**CAT:** Luminous Intensity (mcd)

**HUE:** Dom. Wavelength (nm)


**REF:** Forward Voltage (V)



**Reel Dimensions**




Taping Quantity: 3000pcs



Taping Quantity: 5000pcs & 10000pcs


**Note:** The tolerances unless mentioned is  $\pm 0.1\text{mm}$  , Angle  $\pm 0.5^\circ$  ,Unit = mm

Carrier Tape Dimensions



**Note:** The tolerances unless mentioned is  $\pm 0.1\text{mm}$  , Angle  $\pm 0.5^\circ$  ,Unit = mm

Moisture Resistant Packaging



**Reliability Test Items And Conditions**

The reliability of products shall be satisfied with items listed below.

Confidence level : 90 %

LTPD : 10 %

No.	Items	Test Condition	Test Hours/Cycles	Sample Size	Ac/Rc
1	Reflow	Temp. : 240°C ± 5°C Min. 5 sec.	6 min.	22 Pcs.	0/1
2	Temperature Cycle	H : +100°C 15min. ∫ 5 min. L : -40°C 15min.	300 Cycles	22 Pcs.	0/1
3	Thermal Shock	H : +100°C 5min. ∫ 10 sec. L : -10°C 5min.	300 Cycles	22 Pcs.	0/1
4	High Temperature Storage	Temp. : 100°C	1000 Hrs.	22 Pcs.	0/1
5	Low Temperature Storage	Temp. : -55°C	1000 Hrs.	22 Pcs.	0/1
6	DC Operating Life	I <sub>F</sub> = 20 mA	1000 Hrs.	22 Pcs.	0/1
7	High Temperature / High Humidity	85°C/R.H85%	1000 Hrs.	22 Pcs.	0/1

**Precautions For Use**

1. Over-current-proof

Customer must apply resistors for protection , otherwise slight voltage shift will cause big current change ( Burn out will happen ).

2. Storage time

2.1 The operation of Temperature and RH are : 5°C~35°C , RH60%.

2.2 Once the package is opened, the products should be used within a week.

Otherwise, they should be kept in a damp proof box with desiccating agent.

Considering the tape life , we suggest our customers to use our products within a year(from production date).


2.3 If opened more than one week in an atmosphere 5°C~35°C , RH 60% ,

they should be treated at 60°C± 5°C for 15hrs.


2.4 When you discover that the desiccant in the package has a pink color

(Normal = blue) , you should treat them in the same conditions as 2.3.

**Soldering heat**



**Reflow Temp / Time**



**Soldering Iron**



Basic spec is ≤ 5 sec when 260°C .If temperature is higher, time should be shorter (+10°C → -1sec).

Power dissipation of Iron should be smaller than 15 W , and temperature should be controllable.

Surface temperature of the device should be under 230 °C .

**Rework**

1. Customer must finish rework within 5 sec under 245°C.
2. The head of iron can not touch copper foil.
3. Twin-head type is preferred.

**Thickness of tin paste**

Thickness:  
 $1/2H < T < H$

**EVERLIGHT ELECTRONICS CO., LTD.**  
Office: No 25, Lane 76, Sec 3, Chung Yang Rd,  
Tucheng, Taipei 236, Taiwan, R.O.C

Tel: 886-2-2267-2000, 2267-9936  
Fax: 886-2267-6244, 2267-6189, 2267-6306  
<http://www.everlight.com>