

Komkey Co., Limited

薄膜开关: Membrane switch/Membrane Keyboard
面板: Overlay/Graphic overlay/Label/Decal
面间: Overlay spacer
线间: Circuit spacer
固定层/弹片胶带: dome tape layer
背胶: Adhesive/Glue
线路: Circuit
鼓包: Embossing
弹片: Metal dome
插头: Connector
灯: LED
电阻: Resistor
色号: Colors NO/RAL/PANTON code
手感: Tactile
尺寸: Dimention/Size
背光: LGF Backlight
冷光片: EL
材料: Materials
透明窗口: Transparent window/Clear window
透明红/灰/黑/白: Transparent red/Grey/Black/White
冲穿: Cut out
隐蔽窗口: Dead front window
屏蔽层: Shielding layer
厚度: Thickness
外形: Shape
柔性线路: Flexible printed circuit
硅胶按键: Silicone rubber Keyboard
滴胶: epoxy glue/Drop glue/Dispensing
铝板支撑: Aluminium support
凹凸: Embossing
平面: Flat
亮面: Glossy surface
雾面: Matte surface
底色: Background colors
图案: Artwork
设计图: Design drawing
确认图: Confirmed drawing
防水结构: Water proof construction
按键: Button
丝刷: Silk-Print
面板刮伤: Overlay scratch
彩印: Colors printing
网点印刷: Half-stone printing
7段显示: Seven-Segment window
银点: Silver dots/Silver printing
端子套: Housing
端子: Pin
间距: Pitch
户外防紫外线: Outdoor/UV Stabilized
虚线刀: Dashed line
接触面: Contact side
补强: Stiffener
绝缘层: Insulation layer
按键功能: Switch function
扩散膜: Diffusion film